


Spec Sheet STP21A0300160S



|                   |           |  |
|-------------------|-----------|--|
| Item Number       |           | STP21A0300160S   |
| Standard          |           | KN1031   |
| Material          |           | steel, hardened  |
| Surface           |           | zinc-plated 5-7 $\mu\text{m}$ , baked, blue / transparent passivated |
| Thread Outside-Ø  | <b>d1</b> | 3.00 $^{+0.14}$ mm   |
| Thread Core-Ø     | <b>d2</b> | 1.66 mm  |
| Thread Pitch      | <b>p</b>  | 1.34 mm  |
| Length            | <b>L</b>  | 16.00 $\pm 0.55$ mm  |
| Head-Ø            | <b>D</b>  | 6.00 $_{-0.30}$ mm   |
| Head Height       | <b>K</b>  | 2.100 $\pm 0.125$ mm   |
| Flange Thickness  | <b>S</b>  | 0.70 mm  |
| Thread Run-Out    | <b>X</b>  | 1.50 mm  |
| Radius            | <b>R</b>  | 0.35 mm  |
| Size Cross Recess |           | Z1   |
| Penetration Depth | <b>t</b>  | 1.26 - 1.51 mm   |
| Thread            |           | STS  |
| Weight            |           | 0.685 kg / 1000 pieces   |
| Customs Tariff No |           | 73 181 499   |