

Spec Sheet STP320500700S



|                   |           |  |
|-------------------|-----------|--|
| Item Number       |           | STP320500700S  |
| Standard          |           | KN6032   |
| Material          |           | steel, hardened  |
| Surface           |           | zinc-plated 5-7 µm, baked, blue / transparent passivated |
| Thread Outside-Ø  | <b>d1</b> | 5.00 <sup>+0.15</sup> mm                                 |
| Thread Core-Ø     | <b>d2</b> | 3.53 mm  |
| Thread Pitch      | <b>p</b>  | 1.80 mm  |
| Length            | <b>L</b>  | 70.00 ±0.95 mm   |
| Head-Ø            | <b>D</b>  | 8.80 <sub>-0.36</sub> mm                                 |
| Head Height       | <b>K</b>  | 3.500 ±0.150 mm  |
| Thread Run-Out    | <b>X</b>  | 2.50 mm  |
| Radius            | <b>R</b>  | 0.70 mm  |
| Size Cross Recess |           | H2   |
| Penetration Depth | <b>t</b>  | 2.12 - 2.75 mm   |
| Thread            |           | STS-plus   |
| Weight            |           | 7.736 kg / 1000 pieces                                   |
| Customs Tariff No |           | 73 181 499   |