

Spec Sheet STP39A0350150S



|                            |           |  |
|----------------------------|-----------|--|
| Item Number                |           | STP39A0350150S   |
| Standard                   |           | WN1452   |
| Material                   |           | steel, hardened  |
| Surface                    |           | zinc-plated 5-7 $\mu\text{m}$ , baked, blue / transparent passivated |
| Thread Outside- $\text{Ø}$ | <b>d1</b> | 3.50 $^{+0.18}$ mm   |
| Thread Core- $\text{Ø}$    | <b>d2</b> | 1.91 mm  |
| Thread Pitch               | <b>p</b>  | 1.57 mm  |
| Length                     | <b>L</b>  | 15.00 $\pm 0.55$ mm  |
| Head- $\text{Ø}$           | <b>D</b>  | 6.90 $_{-0.36}$ mm   |
| Head Height                | <b>K</b>  | 2.300 $\pm 0.125$ mm   |
| Thread Run-Out             | <b>X</b>  | 1.80 mm  |
| Radius                     | <b>R</b>  | 0.35 mm  |
| Size Six Lobe              |           | T10  |
| Penetration Depth          | <b>t</b>  | 1.10 - 1.40 mm   |
| Thread                     |           | STS  |
| Weight                     |           | 1.048 kg / 1000 pieces   |
| Customs Tariff No          |           | 73 181 499   |